Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	**410-601/160**	6726.60	**Drain Tap - 1 1/2",** Bayonett socket	0,5 bar	< 160°C	
	410-601/190		**Drain Tap - 1 1/2",** Bayonett socket	0,5 bar	< 190°C	
	410-801/160	6726.80	**Drain Tap - 1 1/2",** Bayonett socket	0,5 bar	< 160°C	
	410-801/190		**Drain Tap - 1 1/2",** Bayonett socket	0,5 bar	< 190°C	
	**411-301/160**	6726.32	**DrainTap - 3/4",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	411-301/190		**DrainTap - 3/4",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-401/160		**DrainTap - 3/4",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	411-401/190		**DrainTap - 3/4",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	**411-501/160**	6726.52	**DrainTap - 1 1/4",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	411-501/190		**DrainTap - 1 1/4",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-601/160	6726.62	**DrainTap - 1 1/2",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	411-601/190		**DrainTap - 1 1/2",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-801/160	6726.82	**DrainTap - 2",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	411-801/190		**DrainTap - 2",** Connection thread Internal threads (IG)	0,5 bar	< 160°C	
	**412-301/160**	6726.34	**DrainTap - 3/4",** Connection thread male threading thread	0,5 bar	< 160°C	
	412-301/190		**DrainTap - 3/4",** Connection thread male threading thread	0,5 bar	< 190°C	
	412-401/160	6726.44	**DrainTap - 1",** Connection thread male threading thread	0,5 bar	< 160°C	
	412-401/190		**DrainTap - 1",** Connection thread male threading thread	0,5 bar	< 190°C	
	**411-605/160**		**DrainTap - 1 1/2",** Connection thread Internal threads with Throw nut	0,5 bar	< 160°C	
	411-605/190		**DrainTap - 1 1/2",** Connection thread Internal threads with Throw nut	0,5 bar	< 190°C	
	411-805/160		**DrainTap - 2",** Connection thread Internal threads with Throw nut	0,5 bar	< 160°C	
	411-805/190		**DrainTap - 2",** Connection thread Internal threads with Throw nut	0,5 bar	< 190°C	

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	**410-602/160**	6726.61	**Drain Tap - 1 1/2",** Bayonett socket with DIN Clamp Connection	0,5 bar	< 160°C	Verwendung an Lebensmittel-pumpen
	410-602/190		**Drain Tap - 1 1/2",** Bayonett socket with DIN Clamp Connection	0,5 bar	< 190°C	Verwendung an Lebensmittel-pumpen
	410-802/160	6726.81	**Drain Tap - 2",** Bayonett socket with DIN Clamp Connection	0,5 bar	< 160°C	Verwendung an Lebensmittel-pumpen
	410-802/190		**Drain Tap - 2",** Bayonett socket with DIN Clamp Connection	0,5 bar	< 190°C	Verwendung an Lebensmittel-pumpen
	**411-602/160**	6726.63	**DrainTap - 1 1/2 ",** Connection thread Internal threads with DIN Clamp Connection	0,5 bar	< 160°C	Verwendung an Lebensmittel-pumpen
	411-602/190		**DrainTap - 1 1/2 ",** Connection thread Internal threads with DIN Clamp Connection	0,5 bar	< 190°C	Verwendung an Lebensmittel-pumpen
	411-802/160	6726.83	**DrainTap - 2 ",** Connection thread Internal threads with DIN Clamp Connection	0,5 bar	< 160°C	Verwendung an Lebensmittel-pumpen
	411-802/190		**DrainTap - 2 ",** Connection thread Internal threads with DIN Clamp Connection	0,5 bar	< 190°C	Verwendung an Lebensmittel-pumpen
	**411-003/190**	6137.00	**DrainTap - 3/8 ",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-003/270		**DrainTap - 3/8 ",** Connection thread Internal threads (IG)	0,5 bar	< 270°C	
	411-203/190		**DrainTap - 1/2 ",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-203/270		**DrainTap - 1/2 ",** Connection thread Internal threads (IG)	0,5 bar	< 270°C	
	411-303/190		**DrainTap - 3/4 ",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-303-270		**DrainTap - 3/4 ",** Connection thread Internal threads (IG)	0,5 bar	< 270°C	
	411-403/190		**DrainTap - 1 ",** Connection thread Internal threads (IG)	0,5 bar	< 190°C	
	411-403/270		**DrainTap - 1 ",** Connection thread Internal threads (IG)	0,5 bar	< 270°C	
	**412-003/190**		**DrainTap - 3/8 ",** Connection thread male threading thread	0,5 bar	< 190°C	
	412-003/270		**DrainTap - 3/8 ",** Connection thread male threading thread	0,5 bar	< 270°C	
	412-203/190		**DrainTap - 1/2 ",** Connection thread male threading thread	0,5 bar	< 190°C	
	412-203/270		**DrainTap - 1/2 ",** Connection thread male threading thread	0,5 bar	< 270°C	
	412-303/190		**DrainTap - 3/4 ",** Connection thread male threading thread	0,5 bar	< 190°C	
	412-303/270		**DrainTap - 3/4 ",** Connection thread male threading thread	0,5 bar	< 270°C	
	412-403/190		**DrainTap - 1 ",** Connection thread male threading thread	0,5 bar	< 190°C	
	412-403/270		**DrainTap - 1 ",** Connection thread male threading thread	0,5 bar	< 270°C	

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
ohne Abbildung	**411-604/000/160**	ähnl. 6625.60	**Safety outflow valve - 1 1/2",** Connection thread internal thread without side exits	0,5 bar	< 160°C	Use on autoclaves
	411-604/000/190	6625.60	**Safety outflow valve - 1 1/2",** Connection thread internal thread without side exits	0,5 bar	< 190°C	Use on autoclaves
	**411-604/010/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread 1 side exit without valve	0,5 bar	< 160°C	Use on autoclaves
	411-604/010/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread 1 side exit without valve	0,5 bar	< 190°C	Use on autoclaves
	**411-604/011/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 setback valve leftside	0,5 bar	< 160°C	Use on autoclaves
	411-604/011/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 setback valve leftside	0,5 bar	< 190°C	Use on autoclaves
	**411-604/012/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 Fat chamber valve leftside	0,5 bar	< 160°C	Use on autoclaves
	411-604/012/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 Fat chamber valve leftside	0,5 bar	< 190°C	Use on autoclaves
ohne Abbildung	**411-604/020/160**	ähnl. 6626.60	**Safety outflow valve - 1 1/2",** Connection thread internal thread 2 side exit without valve	0,5 bar	< 160°C	Use on autoclaves
	411-604/020/190	6626.60	**Safety outflow valve - 1 1/2",** Connection thread internal thread 2 side exit without valve	0,5 bar	< 190°C	Use on autoclaves
	**411-604/021/160**	ähnl. 6626.62.20.20	**Safety outflow valve - 1 1/2",** Connection thread internal thread and 2 setback valve leftside	0,5 bar	< 160°C	Use on autoclaves
	411-604/021/190	6626.62.20.20	**Safety outflow valve - 1 1/2",** Connection thread internal thread and 2 setback valve leftside	0,5 bar	< 190°C	Use on autoclaves
	**411-604/022/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 2 Fat chamber valve leftside	0,5 bar	< 160°C	Use on autoclaves
	411-604/022/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 2 Fat chamber valve leftside	0,5 bar	< 190°C	Use on autoclaves
	**411-604/023/160**	ähnl. 6626.62.21.20	**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve and Fat chamber valve right	0,5 bar	< 160°C	Use on autoclaves
	411-604/023/190	6626.62.21.20	**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve and Fat chamber valve right	0,5 bar	< 190°C	Use on autoclaves
	**411-604/024/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve right , Fat chamber valve left	0,5 bar	< 160°C	Use on autoclaves
	411-604/024/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve right , Fat chamber valve left	0,5 bar	< 190°C	Use on autoclaves
ohne Abbildung	**411-604/111/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve right	0,5 bar	< 160°C	Use on autoclaves
	411-604/111/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and setback valve right	0,5 bar	< 190°C	Use on autoclaves
ohne Abbildung	**411-604/112/160**		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 Fat chamber valve right	0,5 bar	< 160°C	Use on autoclaves
	411-604/112/190		**Safety outflow valve - 1 1/2",** Connection thread internal thread and 1 Fat chamber valve right	0,5 bar	< 190°C	Use on autoclaves

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	**2366/100**		**Grease Foodsafe , 100 gr.** Recommended for Drain taps , after every daily cleaning the cone from the Drain Tap must be greased	410-x01/160 410-x02/160 411-x01/160 411-x02/160 411-x05/160 412-x01/160	< 160°C	
	2366/100/5		**Grease Foodsafe , 5 x 100 gr.** Recommanded for Drain taps , after every daily cleaning the cone from the Drain Tap must be greased		< 160°C	
	**7617/100**		**Grease Foodsafe , 100 gr.** Recommanded for Drain taps , after every daily cleaning the cone from the Drain Tap must be greased	410-x01/190 410-x02/190 411-x01/190 411-x02/190 411-x05/190 412-x01/190 411-x03/190	< 190°C	
	**7619/100**		**Grease Foodsafe , 100 gr.** Recommanded for Drain taps , after every daily cleaning the cone from the Drain Tap must be greased	410-x01/270 410-x02/270 411-x01/270 411-x02/270 411-x05/270 412-x01/270 411-x03/270	< 399°C	
	**410-601/160/01**		**Service Set for Drain Taps :** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 2x - O-Ring 47,29 x 2,62 black 1x - Grease Foodsafe , 2366; 100gr 1x - Service manual	411-50x/160 410-60x/160 411-60x/160	< 160°C	
	410-601/160/02		**Service Set for Drain Taps:** 5x - O-Ring 50 x 4, blue 1x - Grease Foodsafe, 2366; 100gr.	411-50x/160 410-60x/160 411-60x/160	< 160°C	
	410-601/160/03		**Service Set for Drain Taps:** 5x - O-Ring 47,29 x 2,62 blue 1x - Grease Foodsafe, 2366; 100gr.	411-50x/160 410-60x/160 411-60x/160	< 160°C	
	410-601/160/04		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 47,29 x 2,62 black 1x - Stainless Steel Cone 1x - Cone cover 1 1/4" to 1 1/2" 1x - Grease Foodsafe, 2366; 100gr.	411-50x/160 410-60x/160 411-60x/160	< 160°C	
	410-601/190/01		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 2x - O-Ring 47,29 x 2,62 black 1x - Grease Foodsafe, 7617; 100gr. 1x - Service Manual	411-50x/190 410-60x/190 411-60x/190	< 190°C	
	410-601/190/02		**Service Set for Drain Taps:** 5x - O-Ring 50 x 4, blue 1x - Grease Foodsafe, 7617; 100gr.	411-50x/190 410-60x/190 411-60x/190	< 190°C	
	410-601/190/03		**Service Set for Drin Taps:** 5x - O-Ring 47,29 x 2,62 blue 1x - Grease Foodsafe, 7617; 100gr.	411-50x/190 410-60x/190 411-60x/190	< 190°C	
	410-601/190/04		**Serive Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 47,29 x 2,62 black 1x - Stainless Steelm Cone 1x - Cone cover 1 1/4" bis 1 1/2" 1x - Grease Foodsafe, 7617; 100gr.	411-50x/190 410-60x/190 411-60x/190	< 190°C	

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	410-601/270/01		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 2x - O-Ring 47,29 x 2,62 black 1x - Grease Foodsafe , 7619; 100gr. 1x - servcie manual	411-50x/270 410-60x/270 411-60x/270	< 270°C	
	410-601/270/02		**Service Set for Drain Taps:** 5x - O-Ring 50 x 4, blue 1x - Grease Foodsafe, 7919; 100gr.	411-50x/270 410-60x/270 411-60x/270	< 270°C	
	410-601/270/03		**Service Set for Drain Taps:** 5x - O-Ring 47,29 x 2,62 blue 1x - Grease Foodsafe , 7619; 100gr.	410-50x/270 410-60x/270 411-60x/270	< 270°C	
	410-601/270/04		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 47,29 x 2,62 1x - Stainless Steel Cone 1x - Cone cover 1 1/4" bis 1 1/2" 1x - Grease Foodsafe , 7619; 100gr.	411-50x/270 410-60x/270 411-60x/270	< 270°C	
	410-801/160/01		**Service Set for Drain Taps:** 2x - O-Ring 40 x 4,5, blue 1x - O-Ring 62 x 4, blue 2x - O-Ring 60 x 2,5 black 1x - Grease Foodsafe 2366; 100gr 1x - Service Manual	410-80x/160 411-80x/160	< 160°C	
	410-801/160/02		**Service Set for Drain Taps:** 5x - O-Ring 40 x 4,5, blue 1x - Grease Foodsafe, 2366; 100gr.	410-80x/160 411-80x/160	< 160°C	
	410-801/160/03		**Service Set for Drain Taps:** 5x - O-Ring 62 x 4 1x - Spezial-Lebensmittel-Fett, 2366; 100gr.	410-80x/160 411-80x/160	< 160°C	
	**410-801/160/04**		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 60 x 2,5 black 1x - Stainless Steel Cone 1x - Cover for Stainless Steel Cone 2" 1x - Grease Foodsafe , 2366; 100gr.	410-80x/160 411-80x/160	< 160°C	
	410-801/190/01		**Servie Set for Dran Taps:** 2x - O-Ring 40 x 4,5, blue 1x - O-Ring 62 x 4, blue 2x - O-Ring 60 x 2,5 black 1x - Grease Foodsafe, 7617; 100gr 1x - Service Manual	410-80x/190 411-80x/190	< 190°C	
	410-801/190/02		**Service Set for Drain Taps:** 5x - O-Ring 40 x 4,5, blue 1x - Grease Foodsafe, 7617; 100gr.	410-80x/190 411-80x/190	< 190°C	
	410-801/190/03		**Service Set for Drain Taps :** 5x - O-Ring 62 x 4 1x - Grease Foodsafe, 7617; 100gr.	410-80x/190 411-80x/190	< 190°C	
	410-801/190/04		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 60 x 2,5 black 1x - Stainless Steel 1x - Cone cover 2" 1x - Grease Foodsafe 7617; 100gr.	410-80x/190 411-80x/190	< 190°C	

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	410-801/270/01		**Service Set for Drain Taps:** 2x - O-Ring 40 x 4,5, blue 1x - O-Ring 62 x 4, blue 2x - O-Ring 60 x 2,5 1x - Grease Foodsafe 7619; 100gr 1x - Service Manual	410-80x/190 411-80x/190	< 270°C	
	410-801/270/02		**Service Set for Drain Taps:** 5x - O-Ring 40 x 4,5, blue 1x - Grease Foodsafe , 7619; 100gr.	410-80x/190 411-80x/190	< 270°C	
	410-801/270/03		**Service Set for Drain Taps** 5x - O-Ring 62 x 4 1x - Grease Foodsafe, 7619; 100gr.	410-80x/190 411-80x/190	< 270°C	

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	**410-801/270/04**		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 50 x 4, blue 1x - O-Ring 60 x 2,5 1x - Stainless Steel Cone 1x - Cone cover 2" 1x - Grease Foodsafe 7619; 100gr.	410-80x/190 411-80x/190	< 270°C	
	411-203-7/8/160		**Service Set for Drain Taps :** 3x - O-Ring 16 x 3, blau 1x - Grease Foodsafe, 2366; 100gr.	411-003/160 411-203/160	< 160°C	
	411-203-7/8/190		**Service Set for Drain Taps:** 3x - O-Ring 16 x 3, blue 1x - Grease Foodsafe , 7617; 100gr.	411-003/190 411-203/190	< 190°C	
	411-203-7/8/270		**Service Set for Drain Taps:** 3x - O-Ring 16 x 3, blue 1x - Grease Foodsafe , 7619; 100gr.	411-003/270 411-203/270	< 270°C	
	411-403-7/8/160		**Service Set for Drain Taps:** 3x - O-Ring 26 x 3, blue 1x - Grease Foodafe , 2366; 100gr.	411-401/160 411-403/160 412-401/160 412-403/160	< 190°C	
	411-403-7/8/190		**Service Set for Drain Taps:** 3x - O-Ring 26 x 3, blue 1x - Grease Footsafe, 7617; 100gr.	411-401/190 411-403/190 412-401/190 412-403/190 412-303/190	< 190°C	
	411-403-7/8/270		**Service Set for Drain Taps:** 3x - O-Ring 26 x 3, blue 1x - Grease Footsafe, 7619; 100gr.	411-401/270 411-403/270 412-401/270 412-403/270 412-303/270	< 270°C	
	**6726.60-4.1**		**Service Set for Drain Taps:** 2x - O-Ring 35 x 4,5, blue 1x - O-Ring 52 x 4, blue 2x - O-Ring 47,29 x 2,62 1x - Grease Foodsafe , 2366; 20gr.	6726.52 6726.60 6726.61 6726.62 6726.63	< 160°C	
	6726.80-4.1		**Service Set for Drain Taps:** 2x - O-Ring 40 x 4,5, blue 1x - O-Ring 60 x 4, blue 2x - O-Ring 60 x 2,5 1x - Grease Foodsafe , 2366; 20gr.	6726.80 6726.81 6726.82 6726.83	< 160°C	
	**6726-10**		**CLAMP one arch 2"** DN50	411-602/xxx 411-802/xxx		
	6726.61/81		**CLAMP Connection Set**	411-602/xxx 411-802/xxx		
ohne Abbildung	**411-403-4/11**		**Lid for 3/4" & 1" Service Kit**	411-604/xxx/160		
	410-601/160/05		**Lid for 1 1/4" & 1 1/2" complete**	41x-601/160		
	410-801/160/05		**Lid 2" complete**	41x-801/160		
ohne Abbildung	**411-604-2-1**		**Control sleeve**	411-604/xxx/160		
	411-604-2-2		**Spindle TR20x4**	411-604/xxx/160		
	411-604-2-3		**Cone cap**	411-604/xxx/160		
	411-604-2-4		**Cone plate**	411-604/xxx/160		

Gebr. Echtermann GmbH Co. KG
Bertholdstr. 5 | 58644 Iserlohn
Tel.: +49 (0) 2371 / 9582 -0 | www.echtermann.de

echtermann®
for professionals

Stainless Steel Drain Taps

Picture	Article number	Previous	Product discription	max. pressure	max. Temperature	Comments
	411-604-2-5		**Union nut M56x2**	411-604/xxx/160		
	411-604-2-6		**Sealing ring**	411-604/xxx/160		